

SEAMLESS EXTRUDED / AND DRAWN TUBES DIMENSIONS IN INCH

| SEAMLESS EXTRUDED | Wall thickness | .056" | .065" | .120" | .156" | .190" | .250" | .375" | .500" | .750" | 1.000" | 1.250" | 1.500" | 2.000" | 2.170" | | | |
|-------------------|----------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------|--------|--------|--------|--------|--|--|--|
| | Ø Outer | | | | | | | | | | | | | | | | | |
| .827" | | | | | | | | | | | | | | | | | | |
| 1.000" | | | | | | | | | | | | | | | | | | |
| 1.250" | | | | | | | | | | | | | | | | | | |
| 1.500" | | | | | | | | | | | | | | | | | | |
| 2.000" | | | | | | | | | | | | | | | | | | |
| 2.500" | | | | | | | | | | | | | | | | | | |
| 3.000" | | | | | | | | | | | | | | | | | | |
| 3.500" | | | | | | | | | | | | | | | | | | |
| 4.500" | | | | | | | | | | | | | | | | | | |
| 5.500" | | | | | | | | | | | | | | | | | | |
| 6.000" | | | | | | | | | | | | | | | | | | |
| 7.000" | | | | | | | | | | | | | | | | | | |
| 8.000" | | | | | | | | | | | | | | | | | | |
| 9.000" | | | | | | | | | | | | | | | | | | |
| 10.000" | | | | | | | | | | | | | | | | | | |
| 11.000" | | | | | | | | | | | | | | | | | | |
| 12.000" | | | | | | | | | | | | | | | | | | |

| SEAMLESS EXTRUDED AND DRAWN | Wall thickness | .020" | .028" | .035" | .049" | .058" | .083" | .120" | .156" | .200" | .235" | .312" | .375" | .500" | .660" | .750" | 1.000" | | |
|-----------------------------|----------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------|--|--|
| | Ø Outer | | | | | | | | | | | | | | | | | | |
| .187" | | | | | | | | | | | | | | | | | | | |
| .313" | | | | | | | | | | | | | | | | | | | |
| .375" | | | | | | | | | | | | | | | | | | | |
| .500" | | | | | | | | | | | | | | | | | | | |
| .625" | | | | | | | | | | | | | | | | | | | |
| .655" | | | | | | | | | | | | | | | | | | | |
| .750" | | | | | | | | | | | | | | | | | | | |
| 1.000" | | | | | | | | | | | | | | | | | | | |
| 1.500" | | | | | | | | | | | | | | | | | | | |
| 2.500" | | | | | | | | | | | | | | | | | | | |
| 3.000" | | | | | | | | | | | | | | | | | | | |
| 4.000" | | | | | | | | | | | | | | | | | | | |
| 6.000" | | | | | | | | | | | | | | | | | | | |
| 7.000" | | | | | | | | | | | | | | | | | | | |
| 8.000" | | | | | | | | | | | | | | | | | | | |
| 8.500" | | | | | | | | | | | | | | | | | | | |
| 10.000" | | | | | | | | | | | | | | | | | | | |
| 10.240" | | | | | | | | | | | | | | | | | | | |
| 11.000" | | | | | | | | | | | | | | | | | | | |

These charts reflect our standard production possibilities. The exact manufacturing options are dependent on alloy and temper.